

## Specification and scope of supply of P770.35

| Description                                                                                         | Specification/scope of supply                                                                                                                                  |
|-----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Max component length                                                                                | 3500mm                                                                                                                                                         |
| Max component width                                                                                 | 2200mm                                                                                                                                                         |
| Max component thickness                                                                             | 285mm                                                                                                                                                          |
| Max component weight                                                                                | 500kg UDL (Uniformly Distributed Load)                                                                                                                         |
| Measuring accuracy, length & width*                                                                 | +/- 35/75 µm*                                                                                                                                                  |
| Measuring accuracy, height** (optional with Surfscan)                                               | +/- 300 µm                                                                                                                                                     |
| Point Spacing                                                                                       | 0.37mm                                                                                                                                                         |
| Measuring speed**                                                                                   | <0.25sec                                                                                                                                                       |
| Camera                                                                                              | Industrialized ultra high resolution professionally mounted in sealed enclosure                                                                                |
| Computer                                                                                            | Dell, Windows 11                                                                                                                                               |
| Screen                                                                                              | 20 inch flatscreen or better                                                                                                                                   |
| Peripheral equipment                                                                                | Keyboard and optical mouse                                                                                                                                     |
| Proprietary InspecVision software                                                                   | Inspection, SPC, Reporting, Reverse engineering                                                                                                                |
| Data cable                                                                                          | USB2, USB3, CoaXPress or FibreOptic                                                                                                                            |
| KVM                                                                                                 | Keyboard, Video Display & Mouse stand (PC integrated into light table assembly)                                                                                |
| Light table construction                                                                            | Frame with removable sheet metal cladding                                                                                                                      |
| Light table measuring surface                                                                       | Laminate glass, toughened with integral diffusion layer                                                                                                        |
| Light source                                                                                        | LED Strip                                                                                                                                                      |
| Machine Framework Construction                                                                      | Heavy folded and box frame welded sheet metal construction                                                                                                     |
| Power supply                                                                                        | 380V-400V AC 3 phase 4 wire 50/60Hz Other voltages available on request ((16A 230V 3P+N+E IEC 60309 Plug) to (16A 230V 3P+N+E IEC 60309 Socket) Lead supplied) |
| Power consumption                                                                                   | 14 to 21A maximum                                                                                                                                              |
| Protective devices                                                                                  | Circuit breakers, mounted at rear of light table                                                                                                               |
| Control panel                                                                                       | Circuit breakers located in power supply cabinet and computer cabinet                                                                                          |
| EC directives                                                                                       | Compliant with Machinery, Low voltage and EMC Directives                                                                                                       |
| Paint colour (powder paint)                                                                         | RAL5013 (cobalt blue)                                                                                                                                          |
| Ambient operating conditions                                                                        | 10-30 degree C                                                                                                                                                 |
| Approx Footprint/installed width/ depth/ height/ estimated weight of installed Light table and Mast | 4026mm (W) x 3000mm (D) x 6512mm (H) <3500kgs                                                                                                                  |
| Power Supply Electrical Cabinet                                                                     | 803mm (W) x 916mm (D) x 2220mm (H) <250kgs                                                                                                                     |
| Approx Footprint/installed width/ depth/ height/weight of KVM)                                      | 710mm (W) x 474mm (D) x 1740 (H) <100kgs                                                                                                                       |
| Warranty                                                                                            | One year limited warranty on hardware and software                                                                                                             |
| Optional extended warranty                                                                          | Two or three year extended warranty (requires software upgrade option)                                                                                         |
| Software support option                                                                             | Annual support contract provides free software upgrades                                                                                                        |

\*The first accuracy value specifies the accuracy achieved over most of the table, the second accuracy value specifies the accuracy achieved at table edges


\*\*Accuracy results are verified on standard production machines using tests based on ISO 10360

Actual measuring accuracies achieved will depend on operating environment, user input, quality and condition of materials

Errors and omissions excepted

Due to our policy of continuous improvement specifications are subject to change without notice, please contact factory or your InspecVision dealer

Non-standard hardware, software or acceptance tests must be defined prior to purchase



**InspecVision Ltd**

10 Trench Road

Mallusk

Newtownabbey BT36 4TY

Co Antrim, N. Ireland, United Kingdom,

**Telephone:** +44 (0) 28 90 844 012

**Telefax:** +44 (0) 870 706 1614





**Email:** Info@InspecVision.com

**Web Address:** www.InspecVision.com

**Distributor Details:**

# P770.35 Schematic

DIMENSIONS IN BRACKETS ARE IN INCHES  
SCALE: 1:25



## P770.35 Electrical Cabinet

