

Specification and scope of supply of P360.35L

Description	Specification/scope of supply
Max component length	3000mm
Max component width	1220mm
Max component thickness	285mm
Max component weight	500kg
Measuring accuracy, length & width**	+/- 35 / 75 µm*
Measuring accuracy, height** (optional with Surfscan)	+/- 250 µm
Point Spacing	0.33mm
Measuring speed**	<0.25sec
Camera	Industrialized ultra high resolution professionally mounted in sealed enclosure
Computer	Dell, Windows 11
Screen	20 inch flatscreen or better
Peripheral equipment	Keyboard and optical mouse
Proprietary InspecVision software	Inspection, SPC, Reporting, Reverse engineering
Data cable	USB2 or USB3
KVM	Keyboard, Video Display & Mouse stand (PC integrated into light table assembly)
Light table construction	Frame with removable sheet metal cladding
Light table measuring surface	Laminate glass, toughened with integral diffusion layer
Light source	LED Strip
Mast construction	Heavy folded sheet metal construction
Power supply	230 Volt, single phase, 50Hz, (32A 230V IECEE 60309 Plug to 32A 230V IECEE 60309 Socket Lead supplied) or 110 Volt, single phase, 60Hz, (NEMA L5 30P to NEMA L5 30R lead supplied) on request
Power consumption	20 Amp maximum at 230 Volt, 30 Amp max at 110 Volt
Protective devices	Circuit breakers, mounted at rear of light table
Control panel	Control switches for power, camera and lights. Main power indicator
EC directives	Compliant with Machinery, Low voltage and EMC Directives
Paint colour (powder paint)	RAL5013 (cobalt blue)
Ambient operating conditions	10-30 degree C
Approx Footprint/installed width/ depth/ height/ weight of installed Light table and Mast	3347mm (W) x 2199mm (D) x 4607mm (H) <1400kgs
Approx Footprint/installed width/ depth/ height/weight of KVM)	710mm (W) x 474mm (D) x 1740 (H) <100kgs
Standard packing	Export crates suitable for sea shipping (3 nos)
Warranty	One year limited warranty on hardware and software
Optional extended warranty	Two or three year extended warranty (requires software upgrade option)
Software support option	Annual support contract provides free software upgrades

*The first accuracy value specifies the accuracy achieved over most of the table,
the second accuracy value specifies the accuracy achieved in the lower accuracy region, typically at table edges

**Accuracy results are verified on standard production machines using tests based on ISO 10360

Actual measuring accuracies achieved will depend on operating environment, user input, quality and condition of materials

Errors and omissions excepted

Due to our policy of continuous improvement specifications are subject to change without notice, please contact factory or your InspecVision dealer

Non-standard hardware, software or acceptance tests must be defined prior to purchase



InspecVision Ltd

10 Trench Road
Mallusk

Newtownabbey BT36 4TY
Co Antrim United Kingdom

Telephone: +44 (0) 28 90 844 012

Telefax: +44 (0) 870 706 1614

Email: Info@InspecVision.com

Web Address: www.InspecVision.com

Distributor Details:

P360.35L Schematic

DIMENSIONS IN BRACKETS ARE IN INCHES
SCALE: 1:44

